



Atherosclerosis Risk in Communities Study

Cohort Surveillance

Heart Failure Occurrences Data Dictionary

Cohort Surveillance Heart Failure Occurrences Data Dictionary

Occurrence: An occurrence refers to a single hospitalization, fatal or non-fatal, with a unique ID.

Table of Contents

1. Classification Variables	3
1.1. ADHFTYPE_EVER	3
1.2. CHFDIAG	4
1.3. CHFDIAG3.....	6
1.4. HFTYPE_EVER.....	7
1.5. HF_HX.....	8
1.6. INCADHFTYPE_EVER (DO NOT USE).....	9
1.9. INCADHFTYPE_EVER2.....	10
1.10. LVEF_CUR	10
1.11. LVEF_CUR_DAT_FollowUpDays	12
1.12. LVEF_CUR_LOW	13
1.13. LVEF_CUR_SOU.....	14
1.14. LVEF_PRE.....	15
1.15. LVEF_PRE_LOW.....	16
1.16. LVEF_PRE_SOU	17
1.17. LVEF_PRE_YEAR	18
1.17. TRIALISTHF	19
2. Identification Variables	20
2.1. CELB02.....	20
2.2. CENTER	21
2.3. ID	22
2.4. TEACHING	23
3. Demographic / Eligibility Variables.....	24

3.1.	AGE	24
3.2.	RACE1	25
3.3.	SEX	26
3.4.	CSKIPOUT.....	27
4.	Occurrence Follow-up Time Variables.....	28
4.1.	DDATE_FollowUpDays.....	28
4.2.	DDATE_Year	28
4.3.	HFEVTDATE_FollowUpDays.....	29
4.1	HFEVTDATE_Year	29
5	Miscellaneous Variables.....	30
5.1	BMI	30
5.2	BMI_CAT.....	31
5.3	BNP_LAST.....	32
5.4	BNP_WORST.....	33
5.5	EGFREPI_LAST.....	34
5.6	EGFREPI_WORST.....	35
5.7	LOS	36
5.8	TROPONINI_LAST.....	37
5.9	TROPONINI_WORST.....	38
5.10	TROPONINT_LAST.....	39
5.11	TROPONINT_WORST.....	40

1. Classification Variables

1.1. ADHFTYPE_EVER

Purpose

To determine for an acute decompensated heart failure event if this can be classified as heart failure with preserved ejection fraction (HFpEF), systolic heart failure (HFrEF) or recovered.

Description

ADHFTYPE_EVER is a categorical variable. ADHFTYPE_EVER is derived from the variables ADHF, LVEF_CUR_LOW and LVE_PRE_LOW. The classification of the HF occurrence is based on the type of HF(HFDIAG) and the prior (LVEF_PRE_LOW) and current (LVEF_CUR_LOW) ejection fraction data.

Type

Occurrence

Algorithm

If the HF occurrence is NOT classified as {Definite Decompensated HF or Probable Decompensated HF} then set ADHFTYPE_EVER as missing.
If the HF occurrence is classified as {Definite Decompensated HF or Probable Decompensated HF} then set ADHFTYPE_EVER as follows:
If LVEF_CUR_LOW=. and LVEF_PRE_LOW=. then ADHFTYPE_EVER="";
If LVEF_CUR_LOW=. and LVEF_PRE_LOW=0 then ADHFTYPE_EVER="ADHFPEF";
If LVEF_CUR_LOW=. and LVEF_PRE_LOW=1 then ADHFTYPE_EVER="SADHF";
If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=. then ADHFTYPE_EVER="ADHFPEF";
If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=0 then ADHFTYPE_EVER="ADHFPEF";
If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=1 then ADHFTYPE_EVER="RECOVERED";
If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=. then ADHFTYPE_EVER="SADHF";
If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=0 then ADHFTYPE_EVER="SADHF";
If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=1 then ADHFTYPE_EVER="SADHF";

Related Variables

ADHF, HFDIAG, LVEF_CUR_LOW, LVEF_PRE_LOW

1.2. CHFDIAG

Purpose

To determine the final heart failure classification for an occurrence.

Description

CHFDIAG is a character variable. For all cohort heart failure events, MMCC review by two physicians is required. If the diagnoses of the two reviewers are in agreement then this becomes the final classification for the occurrence. If the diagnoses of the two reviews are in disagreement then a third review by an adjudicator is completed and the adjudicator's diagnosis is the final classification for the occurrence.

This is the definitive heart failure classification for an occurrence.

Algorithm

Hospitalizations are reviewed by a single member of the heart failure MMCC with the classification determined by the MMCC reviewer becoming the event's final ARIC classification with the following exception.

a. If the Framingham, NHANES, and Modified Boston computer classification scoring algorithms meet the formula below* AND the heart failure MMCC classification is either "chronic stable heart failure" or "no heart failure", the case is sent to the Chair of the heart failure MMCC for adjudication. The Chair's adjudicated classification becomes the event's final ARIC classification.

* Framingham criteria equal "heart failure present", and NHANES criteria equals "heart failure present", and Modified Boston criteria equal "definite or possible heart failure".

Hospitalizations NOT reviewed by the MMCC:

If BNP (HFAA39a) is greater than 875 pg/ml and:

There is evidence in the doctor's notes that the hospitalization was for HF (HFAA2),

Or

There is evidence of edema (HFAA22a),

Or

There is evidence of basilar rales (HFAA23j),

There is evidence in the doctors notes that the hospitalization was for HF (HFAA2) and:

There is increasing or new onset paroxysmal nocturnal dyspnea (HFAA1c),

Or

There is increasing or new onset orthopnea (HFAA1d),

Or

There is an indication of paroxysmal nocturnal dyspnea during this hospitalization (HFAA23h).

Or

An x-ray showed signs of congestive heart failure during this hospitalization (HFAA28l).

If either criteria #2 or #3 above is met and there is at least one left ventricular function measurement available in the HFA these events are classified as acute decompensated heart failure.

Remarks

This variable was created from HDX form, question 6.

Type

Occurrence

Related Variables

CHFDIAG3

1.3. CHFDIAG3

Purpose

To determine the final heart failure classification for an occurrence.

Description

CHFDIAG3 is a numeric variable. CHFDIAG is similar to CHFDIAG except classifications 'A' and 'B' have been collapsed into one category and classifications 'D' and 'E' have been collapsed into one category.

Type

Occurrence

Algorithm

If CHFDIAG is Definite Decompensated HF or Probable Decompensated HF then CHFDIAG3 = 1
If CHFDIAG is Chronic Stable HF then CHFDIAG = 2
If CHFDIAG is Unlikely HF or Unclassifiable then CHFDIAG3 = 3

SAS Code

```
If CHFDIAG= 'A' or 'B' then CHFDIAG3=1  
If CHFDIAG= 'C' then CHFDIAG3=2  
If CHFDIAG= 'D' or 'E' then CHFDIAG3=3
```

Related Variables

CHFDIAG

1.4. HFTYPE_EVER

Purpose

To determine if a hospitalization can be classified as heart failure with preserved ejection fraction (HFpEF), systolic heart failure(HFrEF) or recovered.

Description

HFTYPE_EVER is a categorical variable. HFTYPE_EVER is calculated from the variables: HFDIAG, LVEF_CUR_LOW and LVEF_PRE_LOW. The classification of the HF occurrence is based on the type of HF(HFDIAG) and the prior (LVEF_PRE_LOW) and current (LVEF_CUR_LOW) ejection fraction data.

Type

Occurrence

Algorithm

If the HF occurrence is not classified as {Definite Decompensated HF, Probable Decompensated HF, Chronic Stable HF} then set HFTYPE_EVER as missing.

If the HF occurrence is classified as {Definite Decompensated HF, Probable Decompensated HF, Chronic Stable HF} then set HFTYPE_EVER as follows:

If LVEF_CUR_LOW=. and LVEF_PRE_LOW=. then HFTYPE_EVER="";

If LVEF_CUR_LOW=. and LVEF_PRE_LOW=0 then HFTYPE_EVER="HFPEF";

If LVEF_CUR_LOW=. and LVEF_PRE_LOW=1 then HFTYPE_EVER="SHF";

If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=. then HFTYPE_EVER="HFPEF";

If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=0 then HFTYPE_EVER="HFPEF";

If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=1 then HFTYPE_EVER="RECOVERED";

If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=. then HFTYPE_EVER="SHF";

If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=0 then HFTYPE_EVER="SHF";

If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=1 then HFTYPE_EVER="SHF";

Related Variables

HFDIAG, LVEF_CUR_LOW, LVEF_PRE_LOW

1.5. HF_HX

Purpose

To determine a prior history of hospitalized heart failure.

Description

HF_HX is a character variable. This variable takes the value from the response abstracted into question 7b of the HFA form.

Type

Occurrence

Algorithm

SAS Code

```
HF_HX=HFAA7b
```

Related Variables

HFAA7b

1.6. INCADHFTYPE_EVER (DO NOT USE)

Purpose

To indicate for a first acute decompensated heart failure with preserved ejection fraction. To determine if a hospitalization can be classified as heart failure with preserved ejection fraction (HFpEF), systolic heart failure (HFrEF) or recovered. As of the Event Year 2024 distribution (hfc24occ1), this variable has been supplanted by INCADHFTYPE_EVER2 and should not be used.

Description

INCADHFTYPE_EVER is a categorical variable. INCADHF_EVER is derived from the variables HF DIAG, INCADHF, LVEF_CUR_LOW, LVEF_PRE_LOW. The classification of the HF occurrence is based on the type of HF(CHFDIAG) , no evidence of prior HF (INCADHF), and the prior (LVEF_PRE_LOW) and current (LVEF_CUR_LOW) ejection fraction data.

Type

Occurrence

Algorithm

If the HF occurrence is NOT classified as {Definite Decompensated HF or Probable Decompensated HF} OR INCADHF ≠ 1 then set INCADHFTYPE_EVER as missing.

If the HF occurrence is classified as {Definite Decompensated HF, Probable Decompensated HF, Chronic Stable HF} AND INCADHF=1 then set INCADHFTYPE_EVER as follows:

If LVEF_CUR_LOW=. and LVEF_PRE_LOW=. then INCADHFTYPE_EVER="";
If LVEF_CUR_LOW=. and LVEF_PRE_LOW=0 then INCADHFTYPE_EVER="INCADHFPEF";
If LVEF_CUR_LOW=. and LVEF_PRE_LOW=1 then INCADHFTYPE_EVER="INCSADHF";
If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=. then INCADHFTYPE_EVER="INCADHFPEF";
If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=0 then INCADHFTYPE_EVER="INCADHFPEF";
If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=1 then INCADHFTYPE_EVER="RECOVERED";
If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=. then INCADHFTYPE_EVER="INCSADHF";
If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=0 then INCADHFTYPE_EVER="INCSADHF";
If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=1 then INCADHFTYPE_EVER="INCSADHF";

Related Variables

CHFDIAG, INCADHF, LVEF_CUR_LOW, LVEF_PRE_LOW

(INCADHF=1 if ADHF=1 and HFAA7b (prior hospitalization for HF)=No or Unknown)

1.9. INCADHFTYPE_EVER2

Purpose

To indicate for a first acute decompensated heart failure with preserved ejection fraction. To determine if a hospitalization can be classified as heart failure with preserved ejection fraction (HFpEF), systolic heart failure (HFrEF) or recovered. The only difference from INCADHFTYPE_EVER is the use of temporary variable INCADHF2 instead of INCADHF (compare the "Related Variables" sections for these two variables).

Description

INCADHFTYPE_EVER2 is a categorical variable. INCADHFTYPE_EVER2 is derived from the variables HFDIAG, INCADHF2, LVEF_CUR_LOW, LVEF_PRE_LOW. The classification of the HF occurrence is based on the type of HF(CHFDIAG), no evidence of prior HF (INCADHF), and the prior (LVEF_PRE_LOW) and current (LVEF_CUR_LOW) ejection fraction data.

Type

Occurrence

Algorithm

If the HF occurrence is NOT classified as {Definite Decompensated HF or Probable Decompensated HF} OR INCADHF2 ≠ 1 then set INCADHFTYPE_EVER2 as missing.

If the HF occurrence is classified as {Definite Decompensated HF, Probable Decompensated HF, Chronic Stable HF} AND INCADHF2=1 then set INCADHFTYPE_EVER2 as follows:

If LVEF_CUR_LOW=. and LVEF_PRE_LOW=. then INCADHFTYPE_EVER2="";
If LVEF_CUR_LOW=. and LVEF_PRE_LOW=0 then INCADHFTYPE_EVER2="INCADHFPEF";
If LVEF_CUR_LOW=. and LVEF_PRE_LOW=1 then INCADHFTYPE_EVER2="INCSADHF";
If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=. then INCADHFTYPE_EVER2="INCADHFPEF";
If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=0 then INCADHFTYPE_EVER2="INCADHFPEF";
If LVEF_CUR_LOW=0 and LVEF_PRE_LOW=1 then INCADHFTYPE_EVER2="RECOVERED";
If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=. then INCADHFTYPE_EVER2="INCSADHF";
If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=0 then INCADHFTYPE_EVER2="INCSADHF";
If LVEF_CUR_LOW=1 and LVEF_PRE_LOW=1 then INCADHFTYPE_EVER2="INCSADHF";

Related Variables

CHFDIAG, INCADHF2, LVEF_CUR_LOW, LVEF_PRE_LOW

(INCADHF2=1 if this is the first occurrence (lowest HFEVTDTE) where ADHF=1 for a given CELB02 (SubjectID). Else INCADHF2=0.)

1.10. LVEF_CUR

Purpose

To indicate the ejection fraction for the current hospitalization.

Description

LVEF_CUR is a continuous variable that is derived from the HFA ejection fraction variables:

HFAA29B, HFAA30B, HFAA32B1, HFAA33B, HFAA34B, HFAA35B and HFAA36C.
Only those variables with test date on or after (arrival date – 90 days) and on or before discharge date are eligible. LVEF_CUR is set to the first non-missing value using the following order:
HFAA29B, HFAA34B, HFAA35B, HFAA33B, HFAA32B1, HFAA36C, HFAA30B.

Type

Occurrence

Algorithm

From the 7 variables:

HFAA29B, HFAA30B, HFAA32B1, HFAA33B, HFAA34B, HFAA35B and HFAA36C select those ones that have their respective date in the time interval:

hospital arrival date (CHIA6A)-90 days <= date <= discharge date (HFAA0C)

Take the first non-missing value using the following order:

HFAA29B, = EF Transthoracic echocardiogram

HFAA34B = EF MRI

HFAA35B = EF CT SCAN

HFAA33B = EF Radionuclide ventriculogram

HFAA32B1 = EF Coronary angiography

HFAA36C = EF Stress test

HFAA30B = EF Transesophageal echocardiogram

Related Variables

HFAA29B, HFAA30B, HFAA32B1, HFAA33B, HFAA34B, HFAA35B,, HFAA36C

LVEF_CUR_DAT, LVEF_CUR_SOU, LVEF_CUR_LOW, LVEF_PRE, HFTYPE_EVER

1.11. LVEF_CUR_DAT_FollowUpDays

Purpose

To indicate the follow-up time in days from v1date to the date of the current ejection fraction.

Description

LVEF_CUR_DAT is a numeric variable. It is the date of the HFA ejection fraction variable from which LVEF_CUR was derived.

Type

Occurrence

Algorithm

If LVEF_CUR was derived from HFAA34B then LVEF_CUR_DAT = HFAA34A
If LVEF_CUR was derived from HFAA35B then LVEF_CUR_DAT = HFAA35A
If LVEF_CUR was derived from HFAA33B then LVEF_CUR_DAT = HFAA33A
If LVEF_CUR was derived from HFAA29B then LVEF_CUR_DAT = HFAA29A
If LVEF_CUR was derived from HFAA30B then LVEF_CUR_DAT = HFAA30A
If LVEF_CUR was derived from HFAA32B1 then LVEF_CUR_DAT = HFAA32A
If LVEF_CUR was derived from HFAA36C then LVEF_CUR_DAT = HFAA36A

Related Variables

HFAA29B, HFAA30B, HFAA32B1, HFAA33B, HFAA34B, HFAA35B,, HFAA36C, LVEF_CUR,
LVEF_CUR_SOU

1.12. LVEF_CUR_LOW

Purpose

To indicate if the current ejection fraction is less than 50.

Description

LVEF_CUR_LOW is an indicator variable. LVEF_CUR_LOW is derived from the variables HDXA5, LVEF_CUR, HFAA29D2, HFAA30C1, HFAA29A and HFAA30A.

LVEF_CUR_LOW takes the first non-missing value in the following hierarchy. The reviewer assessment is the first preference (HDXA5, collapsed across multiple reviewers) then the quantitative abstracted value (LVEF_CUR) and finally the qualitative abstracted value recorded in the variables HFAA29D2 and HFAA30C1.

Type

Occurrence

Algorithm

LVEF_CUR_LOW is the first non-missing value from the following hierarchy: HDXA5 (reviewer qualitative assessment), LVEF_CUR (cut-off is 50%), HFAA29D2 (TTE, qualitative) and HFAA30C1 (TEE, qualitative).

The qualitative variables HFAA29D2 and HFAA30C1 are only considered if their respective dates are in the time interval [hospital arrival date, (CHIA6A)-90 days, discharge date (HFAA0C)]

Related Variables

HDXA5, HFAA29D2, HFAA30C1, LVEF_CUR, HFTYPE_EVER

1.13. LVEF_CUR_SOU

Purpose

To indicate the source of the current ejection fraction.

Description

LVEF_CUR_SOU is a character variable that indicates the current HFA ejection fraction variable from which LVEF_CUR was derived.

Type

Occurrence

Algorithm

If LVEF_CUR was derived from HFAA34B then LVEF_CUR_SOU = ' 34B MRI'
If LVEF_CUR was derived from HFAA35B then LVEF_CUR_SOU = ' 35B CT SCAN'
If LVEF_CUR was derived from HFAA33B then LVEF_CUR_SOU = ' 33B RADIO VENTRI'
If LVEF_CUR was derived from HFAA29B then LVEF_CUR_SOU = ' 29B TRANSTHORACIC'
If LVEF_CUR was derived from HFAA30B then LVEF_CUR_SOU = ' 30B TRANSESOPHAGEAL'
If LVEF_CUR was derived from HFAA32B1 then LVEF_CUR_SOU = '32B1 ANGIOGRAPHY'
If LVEF_CUR was derived from HFAA36C then LVEF_CUR_SOU = '36C STRESS TEST'

Related Variables

HFAA29B, HFAA30B, HFAA32B1, HFAA33B, HFAA34B, HFAA35B,, HFAA36C, LVEF_CUR,
LVEF_CUR_DAT

1.14. LVEF_PRE

Purpose

To indicate the ejection fraction for previous hospitalizations.

Description

LVEF_PRE is a continuous variable. LVEF_PRE is derived from the variables: HFAA29B, HFAA30B, HFAA32B1 and HFAA8A.

Type

Occurrence

Algorithm

Consider continuous ejection fraction variables: HFAA29B, HFAA30B, HFAA32B1 taken during the time interval: [arrival date (CHIA6A)-2 years, arrival date (CHIA6)]. Consider also HFAA8A if its year HFAA8B >= year of the arrival date.

HFA Q29B = EF TTE

HFA Q32B1 = EF Coronary angiography

HFA Q30B = EF TEE

If two values recorded with same imaging modality, give preference to more recent measure. Apply hierarchy based on modality, as defined in LVEF_CUR.

The qualitative variables HFAA29D2 and HFAA30C1 are only considered if their respective dates are in the time interval [CHIA6A)-2 years, arrival date (CHIA6))

Related Variables

HFAA29B, HFAA30B, HFAA32B1, HFAA8A, LVEF_CUR, LVEF_PRE_LOW, LVEF_PRE_SOU, LVEF_PRE_YEAR.

1.15. LVEF_PRE_LOW

Purpose

To indicate if the previous ejection fraction is less than 50.

Description

LVEF_PRE_LOW is an indicator variable. LVEF_PRE_LOW is derived from the variables: HDXA5, LVEF_CUR, HFAA29D2, HFAA30C1, HFAA29A and HFAA30A.

The quantitative abstracted value is the first preference (LVEF_PRE), then the qualitative abstracted value in the variables HFAA29D2, HFAA30C1 and HFAA8A.

Type

Occurrence

Algorithm

LVEF_PRE_LOW is the first non-missing value from the following hierarchy: LVEF_PRE (cut-off is 50%) and then qualitative abstracted value from HFAA29D2 (TTE, qualitative), HFAA30C1 (TEE, qualitative) and HFAA8A (prior imaging).

The qualitative variables HFAA29D2 and HFAA30C1 are only considered if their respective dates are in the time interval [CHIA6A)-2 years, arrival date (CHIA6))

Related Variables

LVEF_PRE, HFAA29D2, HFAA8A, HFAA30C1, HFTYPE_EVER

1.16. LVEF_PRE_SOU

Purpose

To indicate the source of the previous ejection fraction.

Description

LVEF_PRE_SOU is a character variable that indicates the current HFA ejection fraction variable from which LVEF_PRE was derived.

Type

Occurrence

Algorithm

```
IF LVEF_CUR COMES FROM HFAA8A THEN LVEF_CUR_SOU = 'HFAA8A'  
IF LVEF_CUR COMES FROM HFAA29B THEN LVEF_CUR_SOU = '29B TRANSTHORACIC'  
IF LVEF_CUR COMES FROM HFAA30B  
THEN LVEF_CUR_SOU = '30B TRANSESOPHAGEAL'  
IF LVEF_CUR COMES FROM HFAA32B1 THEN LVEF_CUR_SOU = '32B1 ANGIOGRAPHY'
```

Related Variables

HFAA8A, HFAA29B, HFAA30B, HFAA32B1, LVEF_PRE

Remarks:

In the definition of LVEF_PRE, the variable HFAA8A is used even if it missing. This implies that most of the 8987 missing values of LVEF_PRE, correspond to HFAA8A.

1.17. LVEF_PRE_YEAR

Purpose

To indicate the date of the previous ejection fraction.

Description

LVEF_PRE_YEAR is a numeric variable. It is the year of the HFA ejection fraction variable from which LVEF_PRE was derived.

Type

Occurrence

Algorithm

```
IF LVEF_CUR COMES FROM HFAA8A THEN LVEF_CUR_YEAR = HFAA8B  
IF LVEF_CUR COMES FROM HFAA29B THEN LVEF_CUR_YEAR = YEAR(HFAA29A)  
IF LVEF_CUR COMES FROM HFAA30B THEN LVEF_CUR_YEAR = YEAR(HFAA30A)  
IF LVEF_CUR COMES FROM HFAA32B1 THEN LVEF_CUR_YEAR = YEAR(HFAA32A)
```

Related Variables

LVEF_PRE, HFAA8B, HFAA29A, HFAA30A, HFAA32A

1.17. TRIALISTHF

Purpose

To determine a heart failure diagnosis based on selected variables from the HFA form.

Type

Occurrence

Description

TRIALIST is an indicator variable used to classify heart failure based on a modified version of an algorithm developed by the Cardiovascular Clinical Trialists (CCT) Workshop. The criteria were operationalized and automated as described in Loehr et al 2013. The value 1 indicates HF present, and 0 HF absent.

Algorithm

See Loehr et al, 2013.

Related Variables

2. Identification Variables

2.1. CELB02

Purpose

To map a surveillance ID to the Cohort participant ID.

Type

Occurrence

Description

CELB02 is a character variable. CELB02 is the cohort participant ID from question number 2 of the Cohort Event Eligibility (CEL) form. CELB02 is the same for all occurrences within a person.

Related Variables

ID

2.2. CENTER

Purpose

To identify the field center from which a participant for a given occurrence originates

Type

Occurrence

Description

CENTER is a character variable.

2.3. ID

Purpose

To determine an occurrence-level ID for cohort surveillance.

Type

Occurrence

Description

ID is a character variable. ID is a unique identifier for each heart failure occurrence. There may be multiple ID values for the same cohort participant ID (CELB02).

Related Variables

CELB02

2.4. TEACHING

Purpose

To determine an occurrence hospital 's teaching status

Type

Occurrence

Description

TEACHING is a character variable.

Algorithm

See the algorithm under HFAA01A (hospital codes) for details.

Related Variables

HFAA0A

3. Demographic / Eligibility Variables

3.1. AGE

Purpose

To determine a participants age at each occurrence in cohort Surveillance.

Type

Occurrence

Description

AGE is a numeric variable.

Algorithm

SAS Code

```
PREBDAY=not((month(DDATE)>month(DOB1)) or  
(month(DDATE)=month( DOB1) & day(DDATE)>= day( DOB1)));  
AGE=year(DDATE)-year(DOB1)-PREBDAY;
```

Related Variables

DDATE, DOB1

3.2. RACE1

Purpose

To determine the race/ethnicity of a participant for occurrences in cohort surveillance.

Type

Occurrence

Description

RACE1 is a character variable. The value of RACE1 is derived from question number 4 of the Common Hospital Information (CHI) form.

Algorithm

SAS Code

```
RACE1=CHIA4;
```

Related Variables

CHIA4

3.3. SEX

Purpose

To determine a participants sex for occurrences in cohort surveillance.

Type

Occurrence

Description

SEX is a character variable. The value of SEX is derived from question number 3 of the CHI form.

Algorithm

SAS Code

```
SEX=CHIA3;
```

Related Variables

CHIA3

3.4. CSKIPOUT

Purpose

To identify occurrences where the hospital record suggests there are no signs /symptoms indicative of heart failure.

Type

Occurrence

Description

CSKIPOUT is a character variable. CSKIPOUT indicates an occurrence that does not need to be abstracted beyond questions 1, 2, and 3a of the HFA form. These questions are related to the onset of signs and symptoms of heart failure and the presence of an ICD-428 discharge code in the medical record. A response of 'No' to all of these questions suggests the occurrence is not heart failure related.

Algorithm

If HFA questions 1, 2, 3a='No' then CSKIPOUT=1.
Otherwise CSKIPOUT=0.

SAS Code

```
if Celighfa=1 then do;
if (not (hfaa1a="Y"| hfaa1b="Y"| hfaa1c="Y"| hfaa1d="Y"| hfaa1e="Y" or hfaa2="Y")) AND
(hfaa3="N" or hfaa3a="N")
then cskipout=1; else cskipout=0;
cprereview=1- cskipout;
end;
```

Related Variables

HFAA1a, HFAA1b, HFAA1c, HFAA1d, HFAA1e, HFAA2, HFAA3, HFAA3a

4. Occurrence Follow-up Time Variables

4.1. DDATE_FollowUpDays

Purpose

To determine the follow-up time in days since visit 1 and date of discharge for each occurrence.

Type

Occurrence

Description

DDATE is a numeric variable. DDATE is derived from question 0c of the HFA form.

Algorithm

DDATE is taken from the HFA form, Question 0C.

SAS Code

```
DATE=HFAA0c
```

Related Variables

HFAA0c, YEARDOD, V1date01

4.2. DDATE_Year

Purpose

To determine the year of date of discharge for each occurrence.

4.3. HFEVTDATE_FollowUpDays

Purpose

To determine the follow-up time in days since visit 1 and the occurrence date for heart failure cohort surveillance.

Type

Occurrence

Description

HFEVTDATE is a numeric variable. HFEVTDATE is derived from question number 6a of the CHI form. This is the date of admission for each occurrence. IF CHIA6a is missing then the date of discharge is used.

Algorithm

The HFEVTDATE takes the first non-missing date from this ordering of variables (questions on forms CHI, HFA, and CFD): CHIA6a, CHIA0c, HFAA0c, and CFDA0c. If they are all missing then HFEVTDATE is missing.

SAS Code

HFEVTDATE follows this hierarchy:

```
If CHIA6a ne . then HFEVTDATE=CHIA6a;  
Else If CHIA0c ne . then HFEVTDATE= CHIA0c;  
Else If HFAA0c ne . then HFEVTDATE= HFAA0c;  
Else If CFDA0c ne . then HFEVTDATE= CFDA0c;  
Else HFEVTDATE= .;
```

Related Variables

CHIA6a, CHIA0c, HFAA0c, CFDA0c, V1date01

4.1 HFEVTDATE_Year

Purpose

To determine the year of the occurrence date for heart failure cohort surveillance.

5 Miscellaneous Variables

5.1 BMI

Purpose

To determine the body mass index for the current hospitalization.

Type

Occurrence

Description

BMI is a continuous variable. BMI is derived from questions HFAA20b (discharge weight), HFAA20a (admission weight) and HFAA19a, height; after transforming both variables to metric system using the unit information recorded in HFAA20b1, HFAA20a1 and HFAA19a1; BMI is set to $\text{weight}/(\text{height}*\text{height})$.

Algorithm

To calculate weight use discharge weight in metric units (both HFAA20b and HFAA20b1 should not be missing). If any of them is missing use admission weight in metric units (both HFAA20a and HFAA20a1 should not be missing). Calculate height in metric units (both HFAA19a and HFAA19a1 should not be missing). Finally set BMI to $\text{weight}/(\text{height}*\text{height})$.

Related Variables

BMI_CAT

5.2 BMI_CAT

Purpose

To determine the body mass index category for the current hospitalization.

Type

Occurrence

Description

BMI_CAT is a numeric variable. BMI_CAT is derived from BMI. The standard categories are: underweight, normal, overweight and obese.

Algorithm

If BMI is missing set BMI_CAT to missing. If BMI is not missing and less than 18.5 set BMI_CAT to 1 (underweight). If BMI is in the interval [18.5,25) set BMI_CAT to 2 (normal). If BMI is in the interval [25,30) set BMI_CAT to 3 (overweight). If BMI is greater or equal than 30 set BMI_CAT to 4 (obese).

Related Variables

BMI

5.3 BNP_LAST

Purpose

To determine the last laboratory value of brain natriuretic peptide (BNP) for the current hospitalization.

Type

Occurrence

Description

BNP_LAST is a continuous variable. BNP_LAST is derived from question HFAA39b. For all occurrences where HFAA39b is > 5000 then BNP_LAST is set to 5001.

Algorithm

If HFAA39b is missing then set BNP_LAST to missing.

If HFAA39b is >5000 then BNP = 5001.

If HFAA39b is not missing and less than or equal to 5000, set BNP_LAST = HFAA39b.

Related Variables

BNP_WORST

5.4 BNP_WORST

Purpose

To determine the worst laboratory value of brain natriuretic peptide (BNP) for the current hospitalization.

Type

Occurrence

Description

BNP_WORST is a continuous variable. BNP_WORST is derived from question HFAA39a. For all occurrences where HFAA39a is > 5000 then BNP_WORST is set to 5001.

Algorithm

If HFAA39a is missing then set BNP_LAST to missing.

If HFAA39a is >5000 then BNP = 5001.

If HFAA39a is not missing and less than or equal to 5000, set BNP_LAST = HFAA39a

Related Variables

BNP_LAST

5.5 EGFREPI_LAST

Purpose

To determine the last laboratory value of eGFREpi for the current hospitalization.

Type

Occurrence

Description

EGFREPI_LAST is a continuous variable. EGFREPI_LAST is derived from the variables: age, race, sex and Creatinine_last (HFAA44b); using the Epi algorithm defined below.

Algorithm

brace=0;
if race1='B' then brace=1;

If sex='F'
$$\text{EGFREPI_LAST} = 141 * [\min(\text{CREATININE_LAST}/0.7, 1)]^{-0.329} * [\max(\text{CREATININE_LAST}/0.7, 1)]^{-1.209} * (0.993^{\text{age}}) * [\text{brace} * 0.159 + 1] * 1.018$$

If sex='M'
$$\text{EGFREPI_LAST} = 141 * [\min(\text{CREATININE_LAST}/0.9, 1)]^{-0.411} * [\max(\text{CREATININE_LAST}/0.9, 1)]^{-1.209} * (0.993^{\text{age}}) * [\text{brace} * 0.159 + 1]$$

If race1 is missing or equal to 'U' or sex is missing or Creatinine_last is missing set EGFREPI_LAST to missing.

Related Variables

EGFREPI_WORST, CREATININE_LAST, CREATININE_WORST

5.6 EGFREPI_WORST

Purpose

To determine the worst laboratory value of eGFREpi for the current hospitalization.

Type

Occurrence

Description

EGFREPI_WORST is a continuous variable. EGFREPI_WORST is derived from the variables: age, race, sex and Creatinine_worst (HFAA44a); using the Epi algorithm defined below.

Algorithm

brace=0;
if race1='B' then brace=1;

If sex='F'
 $EGFREPI_WORST = 141 * [\min(CREATININE_WORST/0.7, 1)]^{-0.329} * [\max(CREATININE_WORST/0.7, 1)]^{-1.209} * (0.993^{age}) * [brace * 0.159 + 1] * 1.018$

If sex='M'
 $EGFREPI_WORST = 141 * [\min(CREATININE_WORST/0.9, 1)]^{-0.411} * [\max(CREATININE_WORST/0.9, 1)]^{-1.209} * (0.993^{age}) * [brace * 0.159 + 1]$

If race1 is missing or equal to 'U' or sex is missing or Creatinine_worst is missing set EGFREPI_WORST to missing.

Related Variables

EGFREPI_LAST, CREATININE_LAST, CREATININE_WORST

5.7 LOS

Purpose

To determine the length of stay for the current hospitalization.

Type

Occurrence

Description

LOS is an integer variable. LOS is derived as the difference of HFAA0c (discharge date) and CHIA6a (arrival date).

Algorithm

```
If HFAA0c-CHIA6a>=0
  then LOS=HFAA0c-CHIA6a
  else LOS=.
```

Related Variables

5.8 TROPONINI_LAST

Purpose

To determine the last laboratory value of troponin I for the current hospitalization.

Type

Occurrence

Description

TROPONINI_LAST is a numeric variable. TROPONINI_LAST is derived from question number 42b of the HFA form.

Algorithm

IF HFA Question 42b is anything < 0.10 then TROPONINI_LAST = 0.000001. Otherwise TROPONINI_LAST is the response to HFA Question 42b.

Related Variables

TROPONINI_WORST, TROPONINT_LAST, TROPONINT_WORST

5.9 TROPONINI_WORST

Purpose

To determine the worst laboratory value of troponin I for the current hospitalization.

Type

Occurrence

Description

TROPONINI_WORST is a numeric variable. TROPONINI_WORST is derived from question number 42a of the HFA form.

Algorithm

IF HFA Question 42a is anything < 0.10 then TROPONINI_WORST = 0.000001. Otherwise TROPONINI_WORST is the response to HFA Question 42b.

Related Variables

TROPONINI_LAST, TROPONINT_LAST, TROPONINT_WORST

5.10 TROPONINT_LAST

Purpose

To determine the last laboratory value of troponin T for the current hospitalization.

Type

Occurrence

Description

TROPONINT_LAST is a numeric variable. TROPONINT_LAST is derived from question number 41b of the HFA form.

Algorithm

IF HFA Question 41b is anything < 0.1 then TROPONINT_LAST = 0.000001. Otherwise TROPONINT_LAST is the response to HFA Question 41b.

Related Variables

TROPONINT_WORST, TROPONINI_LAST, TROPONINI_WORST

5.11 TROPONINT_WORST

Purpose

To determine the worst laboratory value of troponin T for the current hospitalization.

Type

Occurrence

Description

TROPONINT_WORST is a numeric variable. TROPONINT_WORST is derived from question number 41a of the HFA form.

Algorithm

IF HFA Question 41a is anything < 0.1 then TROPONINT_WORST = 0.000001. Otherwise TROPONINT_WORST is the response to HFA Question 41a.

Related Variables

TROPONINT_LAST, TROPONINI_LAST, TROPONINI_WORST